

# AVS-B2218Z

## 2 MP Indoor/Outdoor, Mid Sized HD-AVS IR Bullet Camera

---



A small form factor bullet, with a serious 'bang' – meet the AVS-B2210. This camera is a weatherproof, day/night, HD-AVS camera. It supports a more conventional bullet design, in a compact housing. The smaller footprint of this camera can make it more desirable in applications where the performance of the camera needs to be as beautiful as it's aesthetics. The camera chassis itself is IP 66 weatherproof, contains a 3.6mm lens, and a 2.0MP imager which outputs a sharp 1080P video stream. This camera is well suited for locations that need a bullet style camera, but the appearance of the camera needs to be minimal. HD-AVS cameras are only compatible with HD-AVS DVR systems, and cannot be used with standard definition recorders. By adopting this latest technology, previously existing analog CCTV systems can rapidly be upgraded to high definition by replacing both cameras and recorders with HD-AVS products!

### Features

- 2.7 ~ 12mm motorized lens
- IR to 90', Smart IR
- IP66
- 60FPS@720, 30FPS@1080
- 12V

# AVS-B2218Z

## Specifications

<b>Model</b>	AVS-B2218Z
<b>Camera</b>	
Image Sensor	1/2.8" 2.4 Megapixel CMOS
Effective Pixels	1984(H)×1225(V)
Electronic Shutter	1/3s ~ 1/100,000s
Frame Rate	30/60fps@720P; 30fps@1080P
Synchronization	Internal
Min. Illumination	0.05Lux@F1.2 (AGC ON), 0Lux IR on
Video Output	1-channel BNC HD-AVS high definition video output / CVBS standard definition video output (Can switch)
<b>Camera Features</b>	
Max. IR LEDs Length	90', Smart IR
Day/Night	Auto (ICR) / Color / B/W
Noise Reduction	2D / 3D
OSD Menu	Support
<b>Lens</b>	
Focal Length	2.7 ~ 12mm motorized
Lens Type	Motorized / Fixed Iris
Mount Type	F14
<b>General</b>	
Power Supply	DC12V±10%
Power Consumption	Max 7.5W
Working Environment	-22°F ~ 140°F/-30°C ~ 60°C; Less than 95%RH (no condensation)
Transmission Distance	1000'
Ingress Protection	IP66
Dimensions	8.38"×3.15"×2.83"/212.85mm×80mm×71.89mm
Weight	1.21lbs/.55kg