

ICIP-B1300

1.3 MegaPixel Full HD Vandal Proof IP Bullet Camera with IR & POE

- 1/3" 1.3 Megapixel Aptina CMOS image sensor
- High-performance TI DaVinci series DSP
- H.264E video compression and JPEG image capture
- 30fps @ 720P resolution, 15fps @ 1.3M(1280x960)
- Dual encoding streams supported
- DC12V power supply, POE
- IP66 Waterproof protection
- Built-in web server, NVR, ICRSS & CMS

Product Overview



Head Office

IC Realtime
3050 N Andrews Ave AXE
Pompano Beach,
FL 33064

Tel: 1 (866) 997-9009
Fax: 1 (954) 827-5900
Email: Info@icrealtime.com
Web: www.icrealtime.com

West Coast Office

IC Realtime
14180 West Van Buren St.
Suite B105
Goodyear, AZ 85338

Tel: 1 (602) 910-3432
Fax: 1 (602) 626 3545
Email: west@icrealtime.com
Web: www.icrealtime.com

ICIP-B1300

1.3 MegaPixel Full HD Vandal Proof IP Bullet Camera with IR & POE

Model	ICIP-B1300
General	
Processor	TI DaVinci Series DSP
Operating System	Embedded LINUX
Resource	Simultaneous remote monitoring, local recording and remote control
User Interface	WEB, CMS(DSS/ PSS), ICRSS, NVR
Camera	
Image Sensor	1/3" 1.3 Megapixel Aptina CMOS image sensor
Effective Pixels	1280 (H)x960(V)
Electronic Shutter	Auto/Manual, 1/60~1/10000s
Mini. Illumination	0.1LUX/F1.2(Color), 0.05LUX/F1.2(B/W) 0LUX(IR On)
Signal Noise Ratio	>50dB
Gain Control	Auto/Manual
White Balance	Auto/Manual
Day/Night	ICR
Lens Mount	M12
Lens	3.6mm
Video	
Video Compression	H.264E/MJPEG
Image Resolution	1.3M(1280x960) / 720P(1280x720) / D1(704x576/704x480)
Encoding Speed	1.3M (1~15fps)+ D1(1~15fps) / 720P(1~30fps)+ D1(1~30fps)
	Extra Stream: D1/CIF (1~30fps)
Bit Rate	128K~8192Kbps
Snapshot	Fastest 1fps JPEG capture
Video Format	NTSC
Network	
Ethernet	RJ-45 (10/100Base-T)
Network Functions	HTTP,TCP/IP,ARP,IGMP,ICMP,RTSP,RTP,UDP,RTCP,SMTP,FTP,DHCP, DNS,DDNS,PPPOE,UPNP,NTP,Bonjour,SNMP
Remote Operation	Monitor, PTZ control, Playback, System setting, File download, Log information, Maintenance & Upgrade
Environmental	
Max. IR Distance	50 ft (20m)
Power	DC12V, PoE, <4W
Ingress Protection	IP66, 4000V thunder, surge and wave protection
Operating Environment	-14°F~140°F / -25°C~+60°C, 10%~90%
Dimensions	Φ2.53" x 5.71" / Φ64.43mm x145.02mm
Weight	0.77lb 0.35kg 12.35oz