

ICIP-D 1300IR

1.3 Megapixel HD Network IR Dome Camera

- 1/3" 1.3MegaPixel Aptina CMOS image sensor
- H.264 & MJPEG dual-stream encoding
- Max 15fps@1.3M(1280x960)&25/30fps@720P(1280x720)
- Day/Night(ICR), 2DNR, AWB, AGC, BLC
- Multiple network monitoring: Web viewer, PSS & ICRSS Pro
- 2.8 mm fixed lens
- Max. IR LEDs Length 60ft
- IP66, PoE

Product Overview



Head Office

IC Realtime
3050 N Andrews Ave AXE
Pompano Beach,
FL 33064

Tel: 1 (866) 997-9009
Fax: 1 (954) 827-5900
Email: Info@icrealtime.com
Web: www.icrealtime.com

West Coast Office

IC Realtime
14180 West Van Buren St.
Suite B105
Goodyear, AZ 85338

Tel: 1 (602) 910-3432
Fax: 1 (602) 626 3545
Email: west@icrealtime.com
Web: www.icrealtime.com

ICIP-D1300IR

1.3 Megapixel HD Network IR Dome Camera

Model	ICIP-D1300	
Camera		
Image Sensor	1/3" 1.3Megapixel Aptina CMOS	
Effective Pixels	1280(H)x960(V)	
Scanning System	Progressive	
Electronic Shutter Speed	Auto/Manual 1/4~1/10000	
Min. Illumination	Color: 0. 1LUX/F1.4, B/W: 0.005LUX/F1.4,0Lux (IR on)	
S/N Ratio	>50dB	
Camera Features		
Max. IR LEDs Length	60FT	
Day/Night	Auto(ICR) / Color / B/W	
Backlight Compensation	BLC	
White Balance	Auto	
Gain Control	Auto/Manual	
Noise Reduction	2D	
Privacy Masking	Up to 4 areas	
Lens		
Focal Length	2.8 mm	
Max Aperture	F1.8(F2.0/F1.8/F1.8)	
Angle of View	H: 70°(114°/46°/35°)	
Mount Type	Board-in Type	
Video		
Compression	H.264 / MJPEG	
Resolution	1.3M(1280x960) / 720P(1280x720) / D1(704x480) / CIF(352x240)	
Frame Rate	1.3M(1~15fps)/720P(1 ~ 25/30fps) Sub Stream: D1/CIF(1 ~ 25/30fps)	
Bit Rate	H.264: 32K ~ 8192Kbps, MJPEG: 32K ~ 12288Kbps	
Network		
Ethernet	RJ-45 (10/100Base-T)	
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour	
ONVIF	ONVIF Ver. 2.0	
Max. User Access	10 users	
Smart Phone	iPhone, iPad, Android, Windows Phone	
General		
Power Supply	DC12V, PoE (802.3af)	

Power Consumption	<4W
Working Environment	-14°F~140°F / -25°C~+60°C, 10%~90%