

ICIP-D 1300VIR

1.3Megapixel 2.8-12mm VF D-WDR HD Vandal-proof IR Network Dome Camera

- 1.3Megapixel D-WDR HD Vandal-proof IR Network Dome Camera
- H.264 & MJPEG dual-stream encoding
- Max 25/30fps@1.3M(1280x960)&25/30fps@720P(1280x720)
- D-WDR, Day/Night(ICR), 2DNR, Auto iris, AWB, AGC, BLC
- Multiple network monitoring: Web viewer, CMS(ICRSS/PSS)
- 2.8~12mm varifocal lens

Product Overview



Head Office

IC Realtime
3050 N Andrews Ave AXE
Pompano Beach,
FL 33064

Tel: 1 (866) 997-9009
Fax: 1 (954) 827-5900
Email: Info@icrealtime.com
Web: www.icrealtime.com

West Coast Office

IC Realtime
14180 West Van Buren St.
Suite B105
Goodyear, AZ 85338

Tel: 1 (602) 910-3432
Fax: 1 (602) 626 3545
Email: west@icrealtime.com
Web: www.icrealtime.com

ICIP-D1300VIR

1.3Megapixel 2.8-12mm VF D-WDR HD Vandal-proof IR Network Dome Camera

Model	ICIP-D1300VIR
Camera	
Image Sensor	1/3" 1.3Megapixel Aptina CMOS
Effective Pixels	1280(H)x960(V)
Scanning System	Progressive
Electronic Shutter Speed	Auto/Manual 1/4~1/10000
Min. Illumination	0.1lux/F1.4(color),0.005Lux/F1.4(B/W),0Lux(IR on)
S/N Ratio	>50dB
Video Output	1 channel, Push Terminal (1.0Vp-p/75Ω)
Camera Features	
Max. IR LEDs Length	60FT
Day/Night	Auto(ICR)/Color/B/W
Backlight Compensation	Off/BLC/HLC/D-WDR(128dB)
White Balance	AUTO
Gain Control	Auto/Manual
Noise Reduction	2D
Privacy Masking	Up to 4 areas
Lens	
Focal Length	2.8~12mm
Max Aperture	F1.4
Focus Control	Manual
Angle of View	H: 92°(Wide)~27.2°(Tele)
Lens Type	Manual/Auto Iris (DC)
Mount Type	Board-in Type
Video	
Compression	H.264 / MJPEG
Resolution	CIF(352x288) / 1.3M(1280x960) / 720P(1280x720) / D1(704x480) / CIF(352x240) /
Frame Rate	Main Stream: 1.3M/720P(1 ~ 25/30fps)
Bit Rate	H.264: 32K ~ 8192Kbps, MJPEG: 32K ~ 12288Kbps
Audio	
Compression	G.711a / G.711u (64kbps)/ PCM(128kbps)
Interface	1/1 channel In/Out
Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour

ONVIF	ONVIF Ver. 2.0
Max. User Access	10 users
Smart Phone	iPhone, iPad, Android, Windows Phone
Auxiliary Interface	
Memory Slot	Micro SD, Max 32GB
Alarm	1/1 channel In/Out
General	
Power Supply	DC12V, PoE(802.3af)
Power Consumption	<8W
Working Environment	-14°F~140°F / -25°C~+60°C, 10%~90%
Protection Level	IK10 & IP66
Dimensions	Φ5.94"x4.68mm ~ Φ151x119mm
Weight	2.31lb ~ 1.05kg