

ICIP-D2000IR

2 Megapixel Full HD Network IR Mini Dome Camera

- 1/3" 2 Megapixel progressive scan Exmor CMOS
- H.264 & MJPEG dual-stream encoding
- 25/30fps@1080P(1920x1080)
- DWDR, Day/Night(ICR), 2DNR, AWB, AGC, BLC
- Multiple network monitoring: Web viewer, CMS(PSS/SmartPSS) & ICRSS
- 3.6mm fixed lens
- Max. IR LEDs Length 60 feet
- IP66, PoE

Product Overview



Head Office

IC Realtime
3050 N Andrews Ave AXE
Pompano Beach,
FL 33064

Tel: 1 (866) 997-9009
Fax: 1 (954) 827-5900
Email: Info@icrealtime.com
Web: www.icrealtime.com

West Coast Office

IC Realtime
14180 West Van Buren St.
Suite B105
Goodyear, AZ 85338

Tel: 1 (602) 910-3432
Fax: 1 (602) 626 3545
Email: west@icrealtime.com
Web: www.icrealtime.com

ICIP-D2000IR

2 Megapixel Full HD Network IR Mini Dome Camera

Model	ICIP-D2000IR	
Camera		
Image Sensor	1/3" 2 Megapixel Exmor CMOS	
Effective Pixels	1920(H)x1080(V)	
Scanning System	Progressive	
Electronic Shutter Speed	Auto/Manual, 1/4~1/10000s	
Min. Illumination	0.1Lux/F1.2 (Color), 0.01Lux/F1.2(B/W);0Lux/F1.2(IR on)	
S/N Ratio	>50dB	
Camera Features		
Max. IR LEDs Length	60 feet	
Day/Night	Auto(ICR)/Color/B/W	
Backlight Compensation	BLC / HLC / DWDR	
White Balance	Auto	
Gain Control	Auto/Manual	
Noise Reduction	2D	
Privacy Masking	Up to 4 areas	
Lens		
Focal Length	3.6mm	
Max Aperture	F1.6	
Angle of View	H:70°(46°)	
Lens Type	Fixed lens	
Mount Type	Board-in Type	
Video		
Compression	H.264 / MJPEG	
Resolution	1080P(1920x1080) / 720P(1280x720) / D1(704x480) / CIF(352x240)	
Frame Rate	25/30fps)	Sub Stream: D1/CIF(1 ~ 25/30fps)
Bit Rate	H.264: 32K ~ 8192Kbps, MJPEG: 32K ~ 20480Kbps	
Network		
Ethernet	RJ-45 (10/100Base-T)	
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour	
ONVIF	ONVIF Ver. 2.0	
Max. User Access	10 users	
Smart Phone	iPhone, iPad, Android, Windows Phone	
General		
Power Supply	DC12V, PoE (802.3af)	
Power Consumption	<5W	

Working Environment	-10°C~+60°C, 10%~90%
Ingress Protection	IP66
Dimensions	Φ113mmx86mm