



## ICR 300W/B



<b>Model</b>	ICR-300H4W
<b>Camera</b>	
Image Sensor	1/2.7" 2.1Megapixel CMOS
Effective Pixels	1928(H)×1088(V)
Electronic Shutter	1/3s~1/300,000s
Video Frame Rate	25/30/50/60fps@720P; 25/30fps@1080P
Synchronization	Internal
Mini. Illumination	0.03Lux/F1.4, 0Lux IR on
Video Output	1-channel BNC HD/AVS high definition video output & CVBS standard definition video output
<b>Camera Features</b>	
Max. IR LEDs Length	180Ft (60m), Smart IR
Day/Night	Auto(ICR) / Color / B/W
Backlight Compensation	120dB True WDR
Noise Reduction	2D/3D
OSD Menu	Multi-language
<b>Lens</b>	
Focal Length	2.7~12mm
Angle of View	H: 99°~37°
Lens Type	Motorized / Fixed Iris
Mount Type	Φ14
<b>General</b>	
Power Supply	DC12V±25%
Power Consumption	Max 10W
Working Environment	-30°C~+60°C / Less than 95%RH (no condensation)
Transmission Distance	Over 500m via 75-3 coaxial cable
Ingress Protection	IP67
Dimensions(W×D×H)	Φ122mm×102mm
Weight	0.55kg
Material	Metal

