



ICR200W/B



Model	ICR-200HW
Camera	
Image Sensor	1/2.7" 2.1Megapixel CMOS
Effective Pixels	1928(H)×1088(V)
Electronic Shutter	1/3s~1/300,000s
Video Frame Rate	25/30/50/60fps@720P; 25/30fps@1080P
Synchronization	Internal
Mini. Illumination	0.03Lux/F2.0, 0Lux IR on
Video Output	1-channel BNC HDAVS high definition video output & CVBS standard definition video output
Camera Features	
Max. IR LEDs Length	150Ft (50m), Smart IR
Day/Night	Auto(ICR) / Color / B/W
Backlight Compensation	120dB True WDR
Noise Reduction	2D/3D
OSD Menu	Multi-language
Lens	
Focal Length	2.8mm
Angle of View	H: 115.6°
Mount Type	M12
General	
Power Supply	DC12V±25%
Power Consumption	Max 5.5W
Working Environment	-30°C~+60°C / Less than 95%RH (no condensation)
Transmission Distance	Over 1500Ft (500m) via 75-3 coaxial cable
Ingress Protection	IP67
Dimensions(W×D×H)	Φ110mm×95mm
Weight	0.3kg
Material	Metal (inner core) + Plastic (outside)