

ICR-220

650TVL(D)/ 700TVL(N) Mini Spy Armor Dome Camera

- 1/3" Sony 960H Ex-view HAD CCD II
- 650TVL(D)/ 700TVL(N)
- New Color Signal Processing for High Color Reproduction
- 2D DNR(Digital Noise Reduction)
- 3.7mm Fixed iris lens(90°/Diagonal)
- Intelligent IR Image Compensation
- 30' IR Beam Distance
- Digital Day & Night
- 3-Axis(All directional mount)
- IP66 Weatherproof
- 12VDC(Tol. 7 ~ 18VDC)

Product Overview



Head Office

IC Realtime
3050 N Andrews Ave AXE
Pompano Beach,
FL 33064

Tel: 1 (866) 997-9009
Fax: 1 (954) 827-5900
Email: Info@icrealtime.com
Web: www.icrealtime.com

West Coast Office

IC Realtime
14180 West Van Buren St.
Suite B105
Goodyear, AZ 85338

Tel: 1 (602) 910-3432
Fax: 1 (602) 626 3545
Email: west@icrealtime.com
Web: www.icrealtime.com

ICR-220

650TVL(D)/ 700TVL(N) Mini Spy Armor Dome Camera

Model	ICR-220
Image sensor	1/3" Sony 960H Ex-view HAD CCD II
Effective Pixels	NTSC : 976(H) x 494(V), PAL : 976(H) x 582(V)
H. Resolution	650TV Lines(Color)/ 700TV Lines(B/W)
Synchronizing system	Internal
Scanning system	NTSC : 525 Lines PAL : 625 Lines 2:1 Interlaced
Video output	1.0Vp-p Composite 75 Ohms
S/N ratio	More than 52dB (AGC Off)
Min. Illumination	0.1Lux(Color), 0.01Lux(B/W)
Shutter Speed	NTSC:1/60~1/100,000 sec. PAL:1/50~1/100,000 sec.
Gamma Correction	Standard $\gamma = 0.45$
White Balance	1,800°K ~ 10,500°K Auto
Gain Control	Standard : -6dB ~ 44.8dB Auto
Smear Effect	0.01%
Power source	12VDC(Tol. 7~18VDC)
Operating current	80mA
Lens(Standard)	3.6mm Fixed iris lens
MTBF	80,000 hours
Iris Control	Electronic
Operating temp./Humidity	-20°C ~ 70°C (Humidity : 0% RH ~ 90% RH)
Measurement	Ø1.97" x 1.74"(H) - Ø50 x 44mm(H)
Weight	0.33lb - 150g