

The ICR 2200 is a high speed PTZ dome camera which can pan a full 360 degrees in 1 second. Having 22X optical zoom and 480 TV lines of resolution the ICR 2200 produces excellent picture quality and extremely high zoom capability. Performance of this camera at night is really something to behold. This PTZ camera incorporates a 1/4" SONY SUPER HAD™ CCD for high sensitivity in extreme low light environments. For optimized sensitivity in both day and night-time shooting applications, the ICR2200 incorporates an Auto ICR (mechanical IR cut filter). With its DSS(digital slow shutter) function ICR2200 takes Day/Night to the next Level. This PTZ can achieve full color in as low as 0.002 LUX. The ICR 2200 is IP66 weatherproof as well as fully vandal proof which make it perfect for all installations both indoor and outdoor.

The ICR 2200 works perfectly with either our Pro or the Flex DVR. It is one of only a few speed domes in the world that has 22X optical zoom capabilities. All of the OSD (on screen display) menus can be accessed directly through the DVR interface. You can set all of the presets as well as tours, patterns and swings via the DVR with no additional joystick or controller. This camera is great when the normal range of a speed domes will just not do.



### Main Features:

- 1/4" Sony SUPER HAD CCD 480 TV Lines
- High Accuracy with Micro-Stepping Control Technology
- Smooth Motion at High Zoom Magnification Mode
- Shortest Path by Vector Drive Technology
- Lightning Speed (MAX. 360°/sec) & Smooth Manual Speed (MIN. 0.05°)
- Lowest Noise & Lowest Vibration
- Day & Night (IR Cut Filter) With DSS
- Low Min. illumination 1.0 Lux (day) / 0.001 Lux (night)
- 220X Zoom Control (Optical 22X, Digital 10X)
- Optional Features: Ceiling, Pole, or Pendant Mount (by request only)
- Additional Accessories: Inside & outside corner mounts (sold seperately)

### Specifications:

- Image Sensor: 1/4" Sony SUPER HAD CCD
- Resolution: 480 TVLines
- Camera: Sony 22X Optical Zoom Camera
- IR Filter: Day & Night (IR Cut Filter) with Digital Slow Shutter
- Min. illumination: 1.0 Lux (day) / 0.001 Lux (night)
- Pan Speed: Endless 360° Pan Rotation at 360° /sec
- Manual Pan Speed: MIN. 0.05°/sec
- Preset: 128 with Alphanumeric labels
- Scan, Tour, Patten: 4 Pattern, 8 Swing and 8 Group Functions
- Privacy Zone: 8 Privacy Zones (Spherical Coordinates)
- Others: Auto Flip, Auto Parking, Power-up Action
- Weatherproof: IP66
- Case: Vandal-Proof case
- OSD: On-Screen Disply on/off
- Motor: High Accuracy with Micro-Stepping Motor (low noise, low vibration)